


COMPACT L 164 Lift up


With standard unsprung hinges. Opening with handle. Automatic version.



ZAnk EP ST

= 100 pcs.

42401010UZ	50
42402010UZ	80
42403010UZ	120





		450		600		900		1200	
h	w	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
230-250		1,2 - 1,3	1 x 80 N	1,6 - 1,8	1 x 120 N	2,4 - 2,6	2 x 50 N	3,2 - 3,5	2 x 80 N
251-300		1,3 - 1,6	1 x 80 N	1,8 - 2,1	2 x 80 N	2,6 - 3,2	2 x 80 N	3,5 - 4,2	2 x 80 N



Rev. 01

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart



	α°
Side bracket in Position A	88°
Side bracket in Position B	71°



The dimensions of the above drilling plan refer to carcasses which use **unsprung hinges** and mounting plates 0 mm.
Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.