


COMPACT L 355 Lift up


With standard unsprung hinges. Opening with handle. Friction version.



ZAnk EP ST

= 100 pcs.



42330010UZ	45
42331010UZ	60
42332010UZ	90
42333010UZ	120




		450		600		900		1200		1500		1800	
h	w	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
400-450	2,1 - 2,4	1 x 45 N		2,8 - 3,2	1 x 45 N	4,2 - 4,7	2 x 45 N	5,6 - 6,3	2 x 45 N	7,0 - 7,9	2 x 45 N	8,4 - 9,5	2 x 60 N
451-500	2,4 - 2,6	1 x 45 N		3,2 - 3,5	1 x 45 N	4,7 - 5,3	2 x 45 N	6,3 - 7,0	2 x 45 N	7,9 - 8,8	2 x 60 N	9,5 - 10,5	2 x 60 N
501-550	2,6 - 2,9	1 x 45 N		3,5 - 3,9	1 x 60 N	5,3 - 5,8	2 x 45 N	7,0 - 7,7	2 x 45 N	8,8 - 9,7	2 x 60 N	10,5 - 11,6	2 x 60 N
551-600	2,9 - 3,2	1 x 60 N		3,9 - 4,2	2 x 45 N	5,8 - 6,3	2 x 60 N	7,7 - 8,4	2 x 60 N	9,7 - 10,5	2 x 90 N		
601-650	3,2 - 3,4	1 x 60 N		4,2 - 4,6	2 x 45 N	6,3 - 6,8	2 x 60 N	8,4 - 9,1	2 x 90 N				
651-700	3,4 - 3,7	1 x 90 N		4,6 - 4,9	2 x 60 N	6,8 - 7,4	2 x 90 N	9,1 - 9,8	2 x 90 N				

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart



	α°
Side bracket in Position A	85°
Side bracket in Position B	83°



The dimensions of the above drilling plan refer to carcasses which use **unsprung hinges** and mounting plates 0 mm.
Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.