


COMPACT L 355 Drop down

With standard sprung hinges. Push to open.



ZAnk
EP
ST

= 100 pcs.

42530010UZ

1200 max		
	Stays	Kg
401-450	2xL 355mm	< 6,3

This chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick using standard, flap or Kimana hinges. These are experimental results to be checked by the customer. **In accordance with the actual European regulation, we suggest to use at least two stays for each door (extra-size doors might require 3 or more gas stays).** For doors whose weights/dimensions are bigger than those reported on the chart, please increase the number of stays accordingly. Please make sure that gas stays are properly regulated in height through the apposite rotary knob so that the weight of the door is equally distributed amongst the stays used. Our technical department is at your disposal to test further cases out of this chart.

Push to open

	α°
Side bracket in Position A	88°
Side bracket in Position B	84°

The dimensions of the drilling plan refer to carcasses which use **standard sprung** and mounting plates 0 mm.

In such case, after the door is initially released by K Push Tech, a manual opening approx. 7cm is required (in order to win the spring resistance). Consequently, the door will automatically open to the fullest.

Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.