


COMPACT L 244 Drop down

With KIMANA hinges. Push to open.



ZAnk	EP	ST	= 100 pcs.
42510010UZ	0		

This chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick using standard, flap or Kimana hinges. These are experimental results to be checked by the customer. **In accordance with the actual European regulation, we suggest to use at least two stays for each door (extra-size doors might require 3 or more gas stays).** For doors whose weights/dimensions are bigger than those reported on the chart, please increase the number of stays accordingly. Please make sure that gas stays are properly regulated in height through the apposite rotary knob so that the weight of the door is equally distributed amongst the stays used. Our technical department is at your disposal to test further cases out of this chart

Push to open

K Push Tech the medium with magnet visible or invisible

Side bracket in Position A	$\alpha^\circ \pm 2^\circ$
Side bracket in Position A	88°
Side bracket in Position B	78°

The dimensions of the above drilling plan refer to carcasses which use Kimana hinges.

VERY IMPORTANT: for Kimana hinges at least 2 Compact stays are required for any door width.

X +	Y +	L1
16 + 4	16 + 2	197
16 + 4	19	199
18 + 2	19	197
19	16 + 2	193
19	19	195
20	20	195

