


COMPACT L 244 Lift up


With standard unsprung hinges. Push to open. Friction version.



ZAnk EP ST

= 100 pcs.





42311010UZ	45
42312010UZ	60
42313010UZ	90
42314010UZ	120



h	w	450		600		900		1200		1500	
		Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
300-350	1,6 - 1,8	1 x 45 N		2,1 - 2,5	1 x 45 N	3,2 - 3,7	1 x 60 N	4,2 - 4,9	2 x 45 N	5,3 - 6,1	2 x 45 N
351-400	1,8 - 2,1	1 x 45 N		2,5 - 2,8	1 x 45 N	3,7 - 4,2	2 x 45 N	4,9 - 5,6	2 x 60 N	6,1 - 7,0	2 x 60 N
401-450	2,1 - 2,4	1 x 60 N		2,8 - 3,2	2 x 45 N	4,2 - 4,7	2 x 45 N	5,6 - 6,3	2 x 60 N	7,0 - 7,9	2 x 90 N
451-500	2,4 - 2,6	1 x 60 N		3,2 - 3,5	2 x 45 N	4,7 - 5,3	2 x 60 N	6,3 - 7,0	2 x 90 N		
501-550	2,6 - 2,9	2 x 45 N		3,5 - 3,9	2 x 60 N	5,3 - 5,8	2 x 90 N	7,0 - 7,7	2 x 120 N		



Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart



	α°
Side bracket in Position A	88°
Side bracket in Position B	81°

Push to open



The dimensions of the drilling plan refer to carcasses which use **standard unsprung** and mounting plates 0 mm.

Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.