







# COMPACT L 164 Drop down

With standard unsprung hinges. Opening with handle.



ZAnk			EP	ST	 = 100 pcs.				
 123		 0		<div>1200 max.</div> <table><tr><th>Stays</th><th>Kg</th></tr><tr><td>225-250</td><td>2xL 164mm &lt; 3,5</td></tr></table>		Stays	Kg	225-250	2xL 164mm < 3,5
Stays	Kg								
225-250	2xL 164mm < 3,5								

This chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick using standard, flap or Kimana hinges. These are experimental results to be checked by the customer. **In accordance with the actual European regulation, we suggest to use at least two stays for each door (extra-size doors might require 3 or more gas stays).** For doors whose weights/dimensions are bigger than those reported on the chart, please increase the number of stays accordingly. Please make sure that gas stays are properly regulated in height through the apposite rotary knob so that the weight of the door is equally distributed amongst the stays used. Our technical department is at your disposal to test further cases out of this chart.

	$\alpha^\circ$
Side bracket in Position A	88°
Side bracket in Position B	71°

The dimensions of the drilling plan refer to carcasses which use **standard unsprung hinges** and mounting plates 0 mm.

Please note that  $\alpha^\circ$  opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.