


COMPACT L 164 Lift up

With standard unsprung hinges. Push to open. Friction version.




ZAnk EP ST

= 100 pcs.

Rev. 01




42301010UZ	45
42302010UZ	60



h	w	450		600		900		1200	
		Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
230-250		1,2 - 1,3	1 x 45 N	1,6 - 1,8	1 x 45 N	2,4 - 2,6	2 x 45 N	3,2 - 3,5	2 x 45 N
251-300		1,3 - 1,6	1 x 45 N	1,8 - 2,1	2 x 45 N	2,6 - 3,2	2 x 45 N	3,5 - 4,2	2 x 45 N



Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart




	α°
Side bracket in Position A	88°
Side bracket in Position B	72°

Push to open



K Push Tech the short with magnet visible or invisible



The dimensions of the drilling plan refer to carcasses which use **standard unsprung** and mounting plates 0 mm.

Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.