


# COMPACT L 244 Lift up


With standard sprung hinges. Opening with handle. Automatic version.



ZAnk EP ST

= 100 pcs.

42410010UZ	50
42412010UZ	80
42413010UZ	100
42414010UZ	120
42415010UZ	140





Rev. 01


h \ w	450		600		900		1200		1500	
	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
300-350	1,6 - 1,8	1 x 80 N	2,1 - 2,5	1 x 80 N	3,2 - 3,7	2 x 50 N	4,2 - 4,9	2 x 80 N	5,3 - 6,1	2 x 100 N
351-400	1,8 - 2,1	1 x 80 N	2,5 - 2,8	2 x 50 N	3,7 - 4,2	2 x 80 N	4,9 - 5,6	2 x 100 N	6,1 - 7,0	2 x 120 N
401-450	2,1 - 2,4	2 x 50 N	2,8 - 3,2	2 x 80 N	4,2 - 4,7	2 x 100 N	5,0 - 6,3	2 x 120 N	7,0 - 7,9	2 x 140 N
451-500	2,4 - 2,6	2 x 80 N	3,2 - 3,5	2 x 80 N	4,7 - 5,3	2 x 100 N				

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.  
These are experimental results to be checked by the customer.  
Our Technical Department is at your disposal to test further cases out of this chart



	$\alpha^\circ$
Side bracket in Position A	86°
Side bracket in Position B	78°



The dimensions of the above drilling plan refer to carcasses which use **standard sprung** and mounting plates 0 mm.  
Please note that  $\alpha^\circ$  opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.