


COMPACT L 164 Lift up


With standard sprung hinges. Push to open. Friction version.



ZAnk EP ST

= 100 pcs.




42301010UZ	45
42302010UZ	60



	450		600		900		1200	
h	Kg	Compact	Kg	Compact	Kg	Compact	Kg	Compact
230-250	1,2 - 1,3	1 x 45 N	1,6 - 1,8	1 x 45 N	2,4 - 2,6	2 x 45 N	3,2 - 3,5	2 x 45 N
251-300	1,3 - 1,6	1 x 45 N	1,8 - 2,1	2 x 45 N	2,6 - 3,2	2 x 45 N	3,5 - 4,2	2 x 45 N



Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart



	α°
Side bracket in Position A	88°
Side bracket in Position B	72°

Push to open



K Push Tech the short with magnet visible or invisible

The dimensions of the drilling plan refer to carcasses which use **standard sprung hinges** and mounting plates 0 mm.
In such case, after the door is initially released by K Push Tech, a manual opening approx. 7cm is required (in order to win the spring resistance).
Please note that α° opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.