







KRABY L 244 Drop down

With standard sprung hinges. Push to open.



<div>ZAnk</div> <div>EP</div> <div>ST</div>			<div> = 100 pcs.</div>					
<div> 42210010UZ</div>	<div></div>	<div><div>N</div><div>0</div></div>	<div></div>	<div><div>1200 max.</div><table><tr><th>Stays</th><th>Kg</th></tr><tr><td>2 x 244 mm</td><td>< 4,9</td></tr></table></div>	Stays	Kg	2 x 244 mm	< 4,9
Stays	Kg							
2 x 244 mm	< 4,9							
			<div><div>301-350</div><div>2 x 244 mm</div><div>< 4,9</div></div>					

This chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick using standard, flap or Kimana hinges. These are experimental results to be checked by the customer. **In accordance with the actual European regulation, we suggest to use at least two stays for each door (extra-size doors might require 3 or more gas stays).** For doors whose weights/dimensions are bigger than those reported on the chart, please increase the number of stays accordingly. Please make sure that gas stays are properly regulated in height through the apposite rotary knob so that the weight of the door is equally distributed amongst the stays used. Our technical department is at your disposal to test further cases out of this chart



For pistons quantity to be specified according to door size, refer to the chart for "KRABY 244 mm - DROP DOWN".