


KRABY L 244 Lift up

With standard unsprung hinges. Push to open. Friction version.



ZAnk EP ST







42011010UZ	45
42012010UZ	60
42013010UZ	90
42014010UZ	120



h	w	450		600		900		1200		1500	
		Kg	Kraby	Kg	Kraby	Kg	Kraby	Kg	Kraby	Kg	Kraby
300-350	1,6 - 1,8	1 x 45 N	2,1 - 2,5	1 x 45 N	3,2 - 3,7	1 x 60 N	4,2 - 4,9	2 x 45 N	5,3 - 6,1	2 x 45 N	
351-400	1,8 - 2,1	1 x 45 N	2,5 - 2,8	1 x 45 N	3,7 - 4,2	2 x 45 N	4,9 - 5,6	2 x 60 N	6,1 - 7,0	2 x 60 N	
401-450	2,1 - 2,4	1 x 60 N	2,8 - 3,2	2 x 45 N	4,2 - 4,7	2 x 45 N	5,6 - 6,3	2 x 60 N	7,0 - 7,9	2 x 90 N	
451-500	2,4 - 2,6	1 x 60 N	3,2 - 3,5	2 x 45 N	4,7 - 5,3	2 x 60 N	6,3 - 7,0	2 x 90 N			
501-550	2,6 - 2,9	2 x 45 N	3,5 - 3,9	2 x 60 N	5,3 - 5,8	2 x 90 N	7,0 - 7,7	2 x 120 N			

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart.



The dimensions of the drilling plan refer to carcasses which use **standard unsprung or negative hinges** and mounting plates 0 mm.
Please note that min and max opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.

For pistons quantity and strength to be chosen according to door size, refer to the chart for "KRABY 244 mm - LIFT UP - Automatic version".