







KRABY L 244 Drop down

With standard unsprung hinges. Opening with handle.



<div>ZAnk</div> <div>EP</div> <div>ST</div>			<div> = 100 pcs.</div>				
<div><div> 123</div><div></div></div> <div>42210010UZ</div>	<div><div></div><div>0</div></div>	<div></div>	<div><div>1200 max.</div><table><tr><th>Stays</th><th>Kg</th></tr><tr><td>301-350 2 x 244 mm</td><td>< 4,9</td></tr></table></div>	Stays	Kg	301-350 2 x 244 mm	< 4,9
Stays	Kg						
301-350 2 x 244 mm	< 4,9						

This chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick using standard, flap or Kimana hinges. These are experimental results to be checked by the customer. **In accordance with the actual European regulation, we suggest to use at least two stays for each door (extra-size doors might require 3 or more gas stays).** For doors whose weights/dimensions are bigger than those reported on the chart, please increase the number of stays accordingly. Please make sure that gas stays are properly regulated in height through the apposite rotary knob so that the weight of the door is equally distributed amongst the stays used. Our technical department is at your disposal to test further cases out of this chart

Magnet K Lock visible or invisible

The dimensions of the drilling plan refer to carcasses which use **unsprung hinges** or **negative hinges** and mounting plates 0 mm.
Please note that min and max opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.