


# KRABY L 355 Lift up

With standard unsprung hinges. Opening with handle. Automatic version.



ZAnk EP ST

= 100 pcs.



42130010UZ	50
42131010UZ	80
42132010UZ	100
42133010UZ	120





Rev. 01

h	W	450		600		900		1200		1500		1800	
		Kg	Kraby	Kg	Kraby	Kg	Kraby	Kg	Kraby	Kg	Kraby	Kg	Kraby
400-450	2,1 - 2,4	1 x 80 N		2,8 - 3,2	2 x 50 N	4,2 - 4,7	2 x 50 N	5,6 - 6,3	2 x 80 N	7,0 - 7,9	2 x 80 N	8,4 - 9,5	2 x 100 N
451-500	2,4 - 2,6	1 x 80 N		3,2 - 3,5	2 x 50 N	4,7 - 5,3	2 x 80 N	6,3 - 7,0	2 x 80 N	7,9 - 8,8	2 x 100 N	9,5 - 10,5	2 x 120 N
501-550	2,6 - 2,9	1 x 80 N		3,5 - 3,9	2 x 50 N	5,3 - 5,8	2 x 80 N	7,0 - 7,7	2 x 100 N	8,8 - 9,7	2 x 120 N		
551-600	2,9 - 3,2	2 x 50 N		3,9 - 4,2	2 x 80 N	5,8 - 6,3	2 x 80 N	7,7 - 8,4	2 x 120 N				
601-650	3,2 - 3,4	2 x 80 N		4,2 - 4,6	2 x 100 N	6,3 - 6,8	2 x 120 N						
651-700	3,4 - 3,7	2 x 80 N		4,6 - 4,9	2 x 100 N	6,8 - 7,4	2 x 120 N						

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick. These are experimental results to be checked by the customer. Our Technical Department is at your disposal to test further cases out of this chart.



The dimensions of the above drilling plan refer to carcasses which use **unsprung hinges** and mounting plates 0 mm. Please note that min and max opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.