


KRABY L 244 Lift up


With standard sprung hinges. Opening with handle. Automatic version.



ZAnk EP ST

= 100 pcs.

42110010UZ	50
42111010UZ	80
42112010UZ	100
42113010UZ	120
42114010UZ	140






Rev. 01

h	w	450	600	900	1200	1500
	Kg	Kraby	Kg	Kraby	Kg	Kraby
300-350	1,6 - 1,8	1 x 80 N	2,1 - 2,5	1 x 80 N	3,2 - 3,7	2 x 50 N
351-400	1,8 - 2,1	1 x 80 N	2,5 - 2,8	2 x 50 N	3,7 - 4,2	2 x 80 N
401-450	2,1 - 2,4	2 x 50 N	2,8 - 3,2	2 x 80 N	4,2 - 4,7	2 x 100 N
451-500	2,4 - 2,6	2 x 80 N	3,2 - 3,5	2 x 80 N	4,7 - 5,3	2 x 100 N

Further newton strengths available on request.

The above chart refers to chipboard or MDF 18 mm doors and aluminium frame doors with glass 4 mm thick.
These are experimental results to be checked by the customer.
Our Technical Department is at your disposal to test further cases out of this chart.



The dimensions of the above drilling plan refer to carcasses which use **standard sprung** and mounting plates 0 mm.
Please note that min and max opening angle shown data is purely indicative. It varies with respect to the hinge brand and adjustment carried out.